14,200 to 16,200 GVWR - Split Tilt Deck - Tandem Axles - 4' Stationary Deck



3600 Series Split Tilt Deck Trailer Models - Tandem Axles - 4' Stationary Deck				
Model Number	3610	3612	3612HD	
Total GVWR (LBS)	14,200	16,200	18,900	
Total Axle Capacity (LBS)	14,000	14,000	16,000	
Payload Capacity (LBS)	10,000	12,000	14,500	
Deck Width	81"	83"	81"	
Deck Length	16' + 24" approach plate	16' + 24" approach plate	16' + 24" approach plate	
Deck Height	25"	25"	25"	
Deck Width Options	None	None	None	
Deck Length Options	None	None	None	

## **FEATURES:**

- Solid 2" White Oak Deck Floor Durable & Long Life
- Heavy Duty Diamond Plate 14 Gauge Steel Fenders Strength and Long Life
- Dexter Heavy Duty Drop Axles EZ Lube Grease Hubs Forward Self-Adjusting Brakes – Equalizers
- Heavy Duty Frame & Tongue Construction
- Sound Structural Design for Long Life and Dependable Performance
- Trailer Low Center of Gravity for Increased Stability, Safety, and Ease of Towing
- TrueTrack Tongue Design Improves Trailer Stability, Responsiveness, and Tracking





**Grandhile** Heavy Duty Equipment Trailers

Rugged

**Heavy Duty** 

Dependable

## Gronkhite FEATURES & SPECIFICATIONS

Capacity Features	3610	3612	3612HD
GVWR - Lbs.	14,200	16,200	18,900
Total Axle Capacity - Lbs.	14,000	14,000	16,000
Payload Capacity - Lbs.	10,000	12,000	14,500
Deck Features	3610	3612	3612HD
Standard Deck Width	81"	83"	81"
Standard Deck Length	Overall 22' (4' stationary 18' tilt includes 2' approach plate)		
Standard Deck Height	25"		
Overall Width	102"		
Overall Length	27' 6"		
Deck Width Options	No		
Filt Deck Length Options	No		
Stationary Deck Length Options	5' or 6'		
Deck Type	Flush Deck Tilt		
Deck Flooring Material	2" White Oak		
Axle & Brake Features	3610	3612	3612HD
Dexter Heavy Duty Axle Size Lbs.	7	,000	8,000
leavy Duty Dexter Axle Type	Tandem 4" Drop Axle		
Slipper Spring Suspension	Yes - Multi Leaf		
oad Equalizers	Yes		
Z Lube Grease Hubs	Yes		
Forward Self-Adjusting Brakes	Yes		
All Wheel Electric Brakes	12" x 2"		12 1/4" x 3 3/8"
Wheel & Tire Features	3610	3612	3612HD
Radial Tires	ST235/80R16 (E) 215/75R17.5 (H)		
Fire Plies	10 Ply 16 Ply		
Disc Type Wheels	8-Bolt		
Wheel Style	Grey		
Frailer Steel Construction Features	3610	3612	3612HD
Mainframe Construction		6"C x 10.5#	1
Bed Frame Construction	6" Channel x 8.2 #		
Prossmember Size	Structural Channel 3" x 4.1#		
Additional Features	3610	3612	3612HD
leavy Duty Tie Downs	10 D Rings		
Hitch	Adj Pintle Eye or Optional 2 5/16 Ball Coupler		
Hitch Height Range	18" to 26"		
Prop Leg Jack Rating	10K Lift - 12K Static		
Diamond Plate Fender with Backs	14 Gauge		
ender Step	Yes		
Sealed Beam LED Lighting	All LED Lighting		
Viring Protection	Steel Conduit		
Viring Junction Box	Yes		
Safety Breakaway System		Yes	
Safety Chains with Hooks		Yes	

Specifications subject to change without notice.